

# USF-HCF

SAFETY ZONE WATER® HIGH CAPACITY UNDER SINK WATER FILTER  
 CONNECTS TO COLD WATER LINE TO FEED FILTERED WATER TO COLD WATER FAUCET  
 (NO DEDICATED FAUCET REQUIRED)

## Follow these easy, simple directions:

1. Close valve on cold water angle stop valve and open cold water faucet to drain cold water line.
2. Install head on filter with screws (provided).
3. Install bracket on side of kitchen cabinet (screws not provided).
4. Insert filter cartridge (1/4 turn.)
5. Disconnect 3/8" braided hose from cold water angle stop valve.



## Continued . . .

6. Connect this hose to the outlet of the filter to feed filtered water to the cold water faucet.
7. Connect the filter's 3/8" braided stainless steel hose to the cold water angle stop valve to feed water to the filter.
8. Open valve on cold water angle stop valve and open cold water faucet.
9. Allow filter to flush until water runs clear.
10. Enjoy filtered water.

Note: Hose fittings are 3/8" compression.

## Removes / reduces:

- Chlorine
- Harmful chemicals
- Tastes
- Odors.

## OUTLET

Disconnect the existing 3/8" braided tubing from the cold water angle stop valve and connect it to the outlet of the filter **to feed filtered water from the filter to the faucet.**

**OUT**



## INLET

Connect the 3/8" tubing attached to the filter to the cold water angle stop **valve to feed tap water to the filter.**

**IN**

## Part Numbers

| Part Number | Description |
|-------------|-------------|
| USF-HC-C    | Cartridge   |
| HSF-HC-HEAD | Head        |
| USF-HC-BKT  | Bracket     |

Dimensions (W x L x D): 4.5" x 20" x 4.5"



[www.safetyzonewater.com](http://www.safetyzonewater.com)

## Components:

1. High capacity filter cartridge (10,000 gallons capacity)
2. Bracket
3. Four mounting screws
4. Filter head (quick connect)
5. 3/8" stainless braided tubing with compression fittings.

**High Capacity Filter**  
**Model: USF-HC-10000**

Replacement cartridge:  
**USF-HC-C**